

## Transportable Multi-gas area monitor



# Detective+ A transportable area monitor you can trust

- Loud and bright alarms
- Inherently rugged and reliable
- Wide sensor options including infra-red
- Built-in pump option
- Folding or fixed legs

Used singly or linked together, Detective+ gives a loud and clear alarm providing effective warning of gas hazards. The rugged, water and impact resistant design and clear display make Detective+ the ideal choice for your transportable gas detection needs.

#### Superb pedigree

- Detective+ is based on the highly successful Triple Plus+ multi-gas monitor which has sold over 55,000 units worldwide

#### Versatile and user friendly

- Infra-red sensors available
  - allows sampling of potentially high flammable gas levels and CO<sub>2</sub>
  - infra-red sensors are unaffected by poisoning
- Built-in pump option provides fast response and extra sensor protection
- Display provides clear information, allows identification of gas hazard
- Easy tracking of multiple hazards
- up to 60 hour battery operation
- Wide range of toxic gas sensors available

#### Extremely loud and clear alarms

- Wailing omni-directional siren, 104 dBA @1 metre
- High intensity red LED clusters provide visual alarm indication
- All linked Detective+ units indicate an alarm sensed by any one unit
- Units actually sensing alarm have faster LED flash
- Audible and visible confidence blip
- Time weighted average alarms for 8 hours and 15 minutes averages

#### Uniquely rugged, tripod construction

- Detectors are fully protected, even if device is overturned
- Raised detectors prevent water ingress
- Easy and quick to set up
- Folding or fixed leg options provide easy storage and transportation

# Detective+

## Specification

Weight	7.5 kg (19lb)		channel)
Dimensions	640 h x 455 w x 455 d mm (25.2 x 17.9 x 17.9 inches)		Logging of events, user and site data
Typical measuring ranges and alarm settings (up to four gas measurement channels)	Standard Range	Typical Alarm Levels	Menu
Flammable gas	0 – 100% LEL	20% LEL	Operating menu allows access to setting up of instrument operation
Oxygen	0 – 25%	19% & 23%	Log Menu allows selection of Users and Sites from predefined lists, marking the log file with an event, and start or stop of data logging
Hydrogen sulphide	0 – 50 ppm	10 ppm	Configuration Menu allows selection of display and alarm modes, setting of alarms, zero and calibration, and selection of flammable gas correction factors from predefined list .
Carbon monoxide	0 – 500 ppm	35 ppm	Battery
Sulphur dioxide	0 – 10 ppm	2 ppm	6 V, 7.2 Ah Sealed lead acid battery pack Optional 6V, 12Ah high capacity pack
Chlorine	0 – 5 ppm	0.5 ppm	Battery life
Nitrogen dioxide	0 – 10 ppm	2 ppm	Standard instrument: Up to 36 hours assuming flammable/CO <sub>2</sub> sensor fitted with 7.2Ah battery. Up to 60 hours with optional 12Ah battery pack
Phosphine	0 – 5 ppm	0.5 ppm	Battery charging
Ammonia	0 – 50 ppm	25 ppm	Built-in battery charging circuit, dual rate 100 – 120 VAC and 200 - 250 V AC Input options available. (Safe Area operation only) Typical charge time: 12 hours
Ammonia	0 – 1000 ppm	N/A	Operating Temp. range
Hydrogen (non-flammable levels)	0 – 2000 ppm	N/A	-20°C to +40°C (-4°F to 104°F). Toxic and Oxygen sensors are not rated for continuous operation at high temperatures. Consult Crowcon if operating temperatures are likely to exceed 40°C (104°F) for extended periods.
Hydrogen cyanide	0 – 25 ppm	10 ppm	Humidity
Hydrogen chloride	0 – 10 ppm	5 ppm	0 – 95% RH non condensing
Chlorine Dioxide	0-1ppm	0.1ppm	Approvals
Hydrogen Fluoride	0-10ppm	1ppm	Europe : ATEX II 2G EEx ib d IIC T4 USA and Canada : Class 1 Division 1 Groups A, B, C, D (Pending)
Ethylene Oxide	0-10ppm	5ppm	Standards
Volatile Organic	0-100ppm	N/A	EN50014, EN50018, EN50020, EN50104, EN45544, UL913 (Pending)
Required ranges and alarms may vary by country and application and these can be configured as required.	Infrared Sensors	Infrared sensors for flammable gas can be supplied as a single range, 0-100% LEL, utilising a single display channel, or as a dual range, 0-100% LEL/0-100% volume, which then occupies two display channels. CO <sub>2</sub> sensors are supplied as 0-5% volume. Only one IR sensor can be fitted, and IR sensors can only be used in combination with oxygen and toxic sensors	Ingress protection
			IP65
			EMC
			EN 50270, FCC CFR47 Part 15, IC ICES03
			PC Interface
			Detective+ has an in-built PC interface, which can be connected to the serial port of a computer using the optional RS232 lead. Portables PC software can be used to set alarms, clock, datalogging interval and password. Portables PC also controls datalogging, giving graphical display of instrument log file and allows file export to spreadsheet.
			Calibration
			Detective+ can be routinely calibrated quickly using its internal menu command, Portables PC or the Crowcon CheckBox IMH management system
			Accessories
			Baffle plate (to protect sensors) Interconnecting lead - 10 m standard, longer lengths up to 100m available Computer lead - RS232 serial link Portables PC software Aspirator Manual bulb and 2 m hose, both non-absorbent and hydrocarbon resistant Internal electric sampling pump option includes external water trap and 2m hose, longer lengths available on request
			Linked Detectives
			Up to 12 units can be linked to provide perimeter or area monitoring
Datalogging	Adjustable sample rate, 100 hours @ 1 minute sample rate (maximum 6000 data points per		