

Testo 410 - Wind or air flow, temperature and humidity



- Available in two models:
 - Testo 410-1** wind or air flow and temperature
 - Testo 410-2** wind or air flow, temperature and humidity
- Integrated 40 mm vane
- Timed mean value calculation
- Hold function and min./max. values
- Windchill calculation for outdoor areas

Technical data

Flow velocity

Measuring range: 0.4 to 20 m/s

Resolution: 0.1 m/s

Accuracy: $\pm (0.2 \text{ m/s} + 2\% \text{ of m.v.})$

Units: m/s, km/h, fpm, mph, knots, perceived

temperature °C/°F
(windchill), Beaufort

Temperature

Measuring range: -10 to 50 °C

Resolution: 0.1 °C

Accuracy: $\pm 0.5 \text{ °C}$

Units: °C/°F

Humidity (testo 410-2 only):

Measuring range: 0 to 100 %rh

Resolution: 0.1 %rh

Accuracy: $\pm 2.5 \text{ %rh}$
(5 to 95 %rh)

Units: %rh, wet bulb, dewpoint

Oper. temp.: -10 to 50 °C

Battery type: Alkaline (2 x AAA)

Battery life: testo 410-1: 100 h.
testo 410-2: 60 h.
(average, without display illumination)

Dimensions

(incl. protective cap): 133 x 46 x 25 mm

Included in delivery:

Calibration protocol · Wrist strap

Belt holder · Protective cap · Batteries

410-1: Part no. 0560 4101

410-2: Part no. 0560 4102